



THE AMERICAN ASSOCIATION FOR
LABORATORY ACCREDITATION

ACCREDITED LABORATORY

A2LA has accredited

ROBB PRECISION TOOL SERVICES, INC.
Lynnwood, WA

for technical competence in the field of

Calibration

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This laboratory also meets the requirements of ANSI/NCSL Z540-1-1994 and any additional program requirements in the field of calibration. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (*refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009*).

Presented this 21st day of May 2009.

A handwritten signature in cursive script, reading "Peter Abney", positioned above a horizontal line.

President
For the Accreditation Council
Certificate Number 2557.01
Valid to May 31, 2011



For the calibrations to which this accreditation applies, please refer to the laboratory's Calibration Scope of Accreditation.

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005
& ANSI/NCSL Z540-1-1994

ROBB PRECISION TOOL SERVICES, INC.
 19015 36th Avenue W., Suite F
 Lynnwood, WA 98036
 Robert Robb Phone: 425 672 7307

CALIBRATION

Valid To: May 31, 2011

Certificate Number: 2557.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following calibrations¹:

I. Mechanical

Parameter/Equipment	Range	Best Uncertainty ² (±)	Comments
Torque Wrenches ³	(2.5 to 50) in•lb (50 to 400) in•lb (400 to 1000) in•lb (25 to 250) ft•lb (251 to 600) ft•lb (601 to 1000) ft•lb (1001 to 2000) ft•lb	1.2 % indicated value (IV) 0.45 % IV 0.6 % IV 0.3 % IV 0.6 % IV 0.4 % IV 0.5 % IV	CDI torque loader and load cells AKO torque loader and load cell
Torque Screwdrivers ³	2.5 in•lb to 40 in•lb	1.2 % IV	CDI torque loader and load cells
Torques Testers, Transducers	(2.5 to 1000) in•lb (25 to 250) ft•lb (251 to 2000) ft•lb	0.5 % IV 0.24 % IV 0.3 % IV	Movement arms, certified weights

¹ This laboratory offers commercial and field calibration service.

² “Best Uncertainty” is the smallest uncertainty of measurement that a laboratory can achieve within its scope of accreditation when performing more or less routine calibrations of nearly ideal measurement standards of nearly ideal measuring equipment. Best uncertainties represent expanded uncertainties expressed at approximately the 95 % level of confidence, usually using a coverage factor of $k = 2$. The best uncertainty of a specific calibration performed by the laboratory may be greater than the best uncertainty due to the behavior of the customer’s device and to influences from the circumstances of the specific calibration.

³ Field calibration service is available for this calibration and this laboratory meets A2LA R104 – *General Requirements: Accreditation of Field Testing and Field Calibration Laboratories* for these calibrations. Please note the uncertainties achievable on a customer's site can normally be expected to be larger than the Best Measurement Capabilities (BMC) that the accredited laboratory has been assigned as Best Uncertainty on the A2LA Scope. Allowance must be made for aspects such as the environment at the place of calibration and for other possible adverse effects such as those caused by transportation of the calibration equipment. The usual allowance for the uncertainty introduced by the item being calibrated, (e.g. resolution) must also be considered and this, on its own, could result in the calibration uncertainty being larger than the BMC.